

►► Built for a Lifetime

## ► Xtreme XL Series



The Xtreme XL Series of CNC routers from Komo Machine has been developed specifically for the customer who expects the utmost in technical quality and reliability. These machines feature a moving table configuration and a side-mounted tool changer.

### Features

- ◆ Four-pole, 18HP (13.2kw), 24,000 RPM, HSK 63F, fan-cooled spindle
- ◆ 12 position automatic tool changer with aggregate capability
- ◆ Air blast for optimal dust/chip evacuation and cooling of the cutting tool
- ◆ Advanced Fanuc HVI servo system tuned for optimum acceleration and deceleration
- ◆ Tool touch-off device with automatic tool data uploading
- ◆ Fanuc Panel i control with integrated PC
- ◆ Universal grid fixture table available in composite (standard) or aluminum (option)
- ◆ Pressurized automatic centralized lubrication system
- ◆ KOMO Production Manager and Machine Monitoring software
- ◆ 19" touch screen display

### Construction

- ◆ FEA "Finite Element Analysis" engineered structure
- ◆ Heavy-duty steel fabrication
- ◆ Closed-loop counterbalance system minimizes plant air consumption

# KOMO

One Komo Drive  
Lakewood, NJ 08701  
www.komo.com

Toll Free: 800-255-5670  
Phone: 732-719-6222  
Fax: 732-579-5443

# Xtreme XL Series - Technical Data

## Spindle

Quantity	One (1)
Type	18HP (13.2kw), four-pole, fan cooled
RPM	Up to 24,000, fully programmable
Taper	HSK 63F

## Table

510	60" x 120" (1524mm x 3048mm)
512	60" x 144" (1524mm x 3658mm)
	Four (4) 1" (25mm) part location pins

## Aggregate-Capable Tool Changer

Max Quantity	12 tools
Max Diameter	3.25" (82mm) positions full; 6.5" (165mm) adjacent positions empty
Max Weight	12 lbs each / 80 lbs total (5.4kg / 36.4kg)
Max Length	5" (127mm)

## Feed Rate/Traverse

X Axis	3150ipm (80mpm)
Y Axis	2300ipm (58.5mpm)
Z Axis	1200ipm (30.5mpm)
Acc/Dec	150 in/sec <sup>2</sup>

## Axis Travel

510	144" (3658mm) x 84" (2134mm) x 10" (254mm)
512	168" (4267mm) x 84" (2134mm) x 10" (254mm)

## Positioning

Accuracy	±0.0008" (0.02mm) linear axis repeatability
----------	---

## Control System

Fanuc Panel i	With integrated PC and 19" touch screen display
---------------	---

## Dust Collection

Interface	6" (152mm) diameter (recommended volume 900 cfm)
-----------	--

## Vacuum System

With low vacuum sensing interface

## Options

Tooling Package	Tool holders, collets, bench top tool changing block, wrench
Vacuum Pumps	Started via pushbutton on main operator panel, with remote start relay
Boring Blocks	Available in a variety of configurations, from nine to 25 spindles
Part Labeling	Print labels directly onto parts prior to machining
Safety Equipment	Laser scanners, light curtains, pressure mats
Material Handling	Automatic material handling system, out feed conveyor, material handling tables
Dual Screen	Additional 19" screen attached to the HMI
Mist Coolant	For cutting non-ferrous metals
C Axis	Allows use of aggregate tooling, for four axis machining capability
Table	Aluminum universal grid, integrated pop-up roller balls